# **SAFETY DATA SHEET**

#### 1. Identification

Product identifier TOOLING FOAM

Other means of identification

Product code 1000023043

Recommended use Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

**Company name** Seamseasy Canada Inc.

Address 4419-66 Street

Camrose, Alberta T4V 2S6

Canada

**Telephone** General Assistance 1-780-995-5506

E-mail Not available.

**Emergency phone number** Emergency - US 1-866-836-8855

Emergency - Outside US 1-952-852-4646

**Supplier** Not available.

#### 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 2

Health hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol.

**Precautionary statement** 

**Prevention** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

1/7

**Response** Wash hands after handling.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards None known.

**Supplemental information** None.

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Isobutane		75-28-5	4.24
Propane		74-98-6	0.76
Other components below	reportable levels		95 0012

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

InhalationSkin contactIf symptoms develop move victim to fresh air. Get medical attention if symptoms persist.Wash off with soap and water. Get medical attention if irritation develops and persists.

Product name: TOOLING FOAM SDS CANADA

Product #: 1000023043 Version #: 01 Issue date: 01-24-2017

**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

**Most important** Direct contact with eyes may cause temporary irritation. symptoms/effects, acute and

Treat symptomatically.

Indication of immediate medical attention and special

delayed

treatment needed

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 5. Fire-fighting measures

Suitable extinguishing media Not available.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment

Firefighters must use standard protective equipment including flame retardant coat, helmet with

and precautions for firefighters

face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened

containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

**Precautions for safe handling** 

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

Product #: 1000023043 Version #: 01 Issue date: 01-24-2017

Occupational exposure limits

**US. ACGIH Threshold Limit Values** 

Components	Туре	Value
Isobutane (CAS 75-28-5)	STEL	1000 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Type

Type

Propane (CAS 74-98-6) **TWA** 1000 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Value

1000 ppm Isobutane (CAS 75-28-5) STEL

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components Value Type **TWA** 

Isobutane (CAS 75-28-5) 800 ppm Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Value Components **Type** 

**TWA** Propane (CAS 74-98-6) 1800 mg/m3 1000 ppm

No biological exposure limits noted for the ingredient(s). **Biological limit values** 

Appropriate engineering

Components

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, controls or other engineering controls to maintain airborne levels below recommended exposure limits. If

exposure limits have not been established, maintain airborne levels to an acceptable level.

Value

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an Respiratory protection

air-supplied respirator.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

**General hygiene** considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

**Appearance** 

Physical state Gas. Aerosol. Form Not available. Color Odor Not available. **Odor threshold** Not available. Not available. pН Not available. Melting point/freezing point

Initial boiling point and boiling

range

201.53 °F (94.18 °C) estimated

-99.4 °F (-73.0 °C) Propellant estimated Flash point

Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

Not available.

(%) Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

26.31 psig @70F estimated

Product name: TOOLING FOAM SDS CANADA Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** 860 °F (460 °C) estimated

Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive.

Heat of combustion (NFPA 2.16 kJ/g estimated

30B)

Oxidizing properties Not oxidizing.

Percent volatile 99.29 % estimated

Specific gravity 0.979 estimated

### 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

#### 11. Toxicological information

Information on likely routes of exposure

InhalationNo adverse effects due to inhalation are expected.Skin contactNo adverse effects due to skin contact are expected.Eye contactDirect contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Species

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

Acute toxicity

Components

Components	Opecies	rest itesuits
Isobutane (CAS 75-28-5)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l

**Test Results** 

Product name: TOOLING FOAM SDS CANADA

Components **Species Test Results** 

658 mg/l/4h

\* Estimates for product may be based on additional component data not shown.

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Not available. Carcinogenicity

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard** 

### 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

Isobutane 2.76 2.36 Propane

No data available. **Mobility in soil** 

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents **Disposal instructions** 

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

## 14. Transport information

TDG

UN1950 **UN** number AEROSOLS, flammable

**UN proper shipping name** Transport hazard class(es)

Class

2.1 **Subsidiary risk** 

Packing group Not applicable.

**Environmental hazards** 

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity.

Product name: TOOLING FOAM SDS CANADA

#### **IATA**

UN number UN1950

**UN proper shipping name** Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

**IMDG** 

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No. EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling. Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

IATA; IMDG; TDG



## 15. Regulatory information

# Canadian regulations

**Controlled Drugs and Substances Act** 

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

**Precursor Control Regulations** 

Not regulated.

## International regulations

### **Stockholm Convention**

Not applicable.

Product name: TOOLING FOAM SDS CANADA

#### **Rotterdam Convention**

Not applicable.

**Kyoto protocol** 

Not applicable.

**Montreal Protocol** 

Not applicable. **Basel Convention** 

Not applicable.

### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

### 16. Other Information

Issue date 01-24-2017

Version # 01

United States & Puerto Rico

**Disclaimer** We cannot anticipate all conditions under which this information and its product, or the products of

other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written

Yes

7/7

based on the best knowledge and experience currently available.

**Revision information** Product and Company Identification: Product and Company Identification

Hazard(s) identification: Hazard statement Hazard(s) identification: Prevention

Product name: TOOLING FOAM SDS CANADA

Product #: 1000023043 Version #: 01 Issue date: 01-24-2017

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).